

# PREVENT COSTLY SLIPS



## SELF ADHESIVE ANTI-SLIP TAPES

To be applied to surfaces where there may be a safety hazard due to slipping either in or out of doors.

Our self adhesive tapes are tough & durable and provides an excellent slip resistance because of the grip provided by the grit surface of the tape.

Constructed of mineral coated plastic film, one side pressure sensitive adhesive protected by a removable liner.

**SURFACE PREPARATION:** Apply tape only to a clean, dry, grease & dust free surface. Press firmly into position to obtain maximum benefit from the pressure sensitive adhesive. Best adhesion at 23C. At low temperatures there is a chance of condensation forming & the tack of the adhesive can be reduced.

**ROLL SIZES:** 18.3 metres in length.

**COLOURS:** Black available in 12mm, 25mm, 50mm, 100mm, 150mm & 300mm widths.

Yellow available in 12mm, 25mm, 50mm, 100mm, 150mm, 200mm & 300mm widths.

Glow-in-the-dark available in 12mm, 25mm & 50mm widths.

White, Green, Yellow/Black stripe, Grey, Clear Heavy Duty available in 25mm & 50mm widths.

**Non-Abrasive** clear anti-slip tape available in 25mm & 50mm widths.

Also available: Self adhesive anti-slip mats 150mm x 600mm

“Watch Your Step”

“Caution”

Black mat with Glow- in- the- dark strip.

TECHNICAL DATA :	MINERAL PARTICLES	-	Aluminium Oxide
	GRADE	-	Course grit 24 & 36
			Medium 60
	HOLDING MEDIUM	-	Solvent acrylic adhesive
	APPLICATION TEMP	-	5 up to 50C
	ADHESION	-	600gm/cm
	THICKNESS	-	0.8 MM +/-0.2mm
	TENSILE STRENGTH	-	7 KgF/25mm
	ELONGATION AT BREAK-	-	80%
	RESISTANCE TO WEAR	-	12 months
	RESISTANCE TO GREASE	-	8 months
	STAINING OF ADHESIVE	-	No evidence of migration